

PROJECT	TYPE NO.	DATE

## SURFACE-MOUNTED FLOODLIGHT

# DRACO-260



IP65



GREY

### HOUSING

Aluminium Die-Cast  
Imports of Rubber Seals  
Aluminium Profiles Recliner Bracket  
Alternatively Square Aluminium Die-Cast Installation Disk  
Stainless Steel Screws

### LENS

High-Strength Tempered Glass Face

### LED MODULE

Cree

### DRIVER

Built-in LED

### DIMMING OPTIONS

DMX or 1V-10V

### BEAM ANGLE OPTIONS

12°, 25°, 45°, 18°x40°

### INPUT VOLTAGE

100V-240V AC/50Hz-60Hz

### OPERATING TEMPERATURE RANGE

-20°C to +40°C

### MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

### DRIVER LIFETIME

50,000 hours

### SYSTEM WARRANTY

5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
DRC-260	CREE	3240lm	40W	≥80	3000K	25°	ø175 x 200mm
		3710lm			4000K		
		3960lm			6000K		
		3080lm			R.G.B		

PHOTOMETRIC DATA	SECTION SIZE
<p>CREE COB 40W - 25°</p>	
OPTIONAL ACCESSORIES	
<p>HOOD</p>	