

PROJECT	TYPE NO.	DATE

WALL-MOUNTED UP/DOWNLIGHT

NIXIE-227



IP54



GREY

HOUSING

Aluminium Lighting

LENS

High-Strength Tempered Glass Face

LED MODULE

Cree

DRIVER

Built-in LED

DIMMING OPTIONS

DALI, Touch Dim, DSI or 1V-10V

INPUT VOLTAGE

100V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE RANGE

-20°C to +40°C

MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

DRIVER LIFETIME

50,000 hours

SYSTEM WARRANTY

5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
NXE-227	CREE	2 x 720lm	22W	≥80	3000K	18° or 36°	ø120 (204) x 275 + (125 x 147)mm
		2 x 810lm			4000K		
		2 x 870lm			5000K		

PHOTOMETRIC DATA	SECTION SIZE
<p>CREE COB 22W – 18°</p> <p>CREE COB 22W – 36°</p>	<p>125 x 147mm</p> <p>275mm</p> <p>ø120mm</p> <p>204mm</p>