






PROJECT	TYPE NO.	DATE

TROFFER

SLICE-S4

 IP20
 F
 CE

 WHITE

- CONSTRUCTION**
Cold rolled Sheet Steel
Electrostatically applied Powder Coat
- DIFFUSER**
Linear fully Frosted Acrylic Lens
- LENS OPTIONS**
Low-Glare Micro Prismatic or Frosted Micro Prismatic
- LED MODULE**
Osram
- DRIVER**
Philips, Osram, Tridonic
- DIMMING OPTIONS**
DALI, Touch Dim, DSI or 1V-10V
- INPUT VOLTAGE**
220V-240V AC/50Hz-60Hz
- OPERATING TEMPERATURE RANGE**
-20°C to +40°C
- MAINTENANCE OF LUMEN**
L70 50,000 hours at 25°C
- DRIVER LIFETIME**
50,000 hours
- SYSTEM WARRANTY**
5 years
- AVAILABLE WITH**
- Air Slots
 - Bespoke Sizing
 - Surface-Mounting Kits
 - Plaster-Recess Kits



MODEL	LED	LED LUMEN	SYS. POWER	CRI	CCT	DIMENSIONS
SLC-S4	OSRAM	2200lm	17.8W	≥80	4000K	595 x 295 x 32mm

PHOTOMETRIC DATA	SECTION SIZE
