

| PROJECT | TYPE NO. | DATE |
|---------|----------|------|
| | | |

DOWNLIGHT

EROS-322



IP65



ø115mm



BLACK



GREY



WHITE

TRIM

Aluminum Die-Cast
Electrostatically applied Powder Coat

FRAME

Steel

HEAT SINK

Aluminum Anodised Coating

REFLECTOR

Aluminum Anodised Specular Silver

LED MODULE

Cree

DRIVER

Remote Philips

DIMMING OPTIONS

DALI, Phase Cut, 1V-10V, Touch Dim

INPUT VOLTAGE

220V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE

RANGE -20°C to +40°C

MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

DRIVER LIFETIME

50,000 hours

SYSTEM WARRANTY

5 years



| MODEL | LED | LUM. LUMENS* | SYS. POWER* | CRI | CCT | BEAM ANGLE | DIMENSIONS |
|---------|------|--------------|-------------|-----|-------|---------------|--------------|
| ERS-322 | CREE | 1800lm | 20W | ≥80 | 3000K | 25°, 30°, 45° | ø125 x 120mm |
| | | 1880lm | | | 4000K | | |
| ERS-322 | CREE | 2100lm | 24W | ≥80 | 3000K | 25°, 30°, 45° | ø125 x 120mm |
| | | 2200lm | | | 4000K | | |

SECTION SIZE

