









PROJECT	TYPE NO.	DATE

ADJUSTABLE DOWNLIGHT

ORBIT-308

-  IP20
-  F
CE
-  Aluminum Anodised Coating
-  Reflector
-  LED MODULE
ø85mm
-  20° 20°
-  BLACK
-  WHITE

TRIM
Aluminium Die-Cast
Electrostatically applied Powder Coat

FRAME
Steel

HEAT SINK
Aluminium Anodised Coating

REFLECTOR
Aluminium Anodised Specular Silver

LED MODULE
Cree, Optional: Philips, Osram, Tridonic

DRIVER
Remote Philips, Osram, Tridonic

DIMMING OPTIONS
DALI, Touch Dim, DSI or 1V-10V

INPUT VOLTAGE
220V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE RANGE
-20°C to +40°C



MAINTENANCE OF LUMEN
L70 50,000 hours at 25°C

DRIVER LIFETIME
50,000 hours

SYSTEM WARRANTY
5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
ORB-308	CREE	700lm	8W	≥80	3000K	18°, 24°, 36°	ø95 x 93.5mm
		750lm			4000K		
ORB-308	CREE	1250lm	14W	≥80	3000K	18°, 24°, 36°	ø95 x 93.5mm
		1300lm			4000K		

PHOTOMETRIC DATA	SECTION SIZE												
<p>CREE COB 14W - 36°</p> <table border="1"> <thead> <tr> <th>H [m]</th> <th>Max [lux]</th> <th>φ [mm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2501</td> <td>670</td> </tr> <tr> <td>2</td> <td>625</td> <td>1350</td> </tr> <tr> <td>3</td> <td>277</td> <td>2020</td> </tr> </tbody> </table> 	H [m]	Max [lux]	φ [mm]	1	2501	670	2	625	1350	3	277	2020	 <p>93.5mm</p> <p>ø95mm</p>
H [m]	Max [lux]	φ [mm]											
1	2501	670											
2	625	1350											
3	277	2020											