

PROJECT	TYPE NO.	DATE

## SUSPENDED DOWNLIGHT

# TAURUS-135X



IP20



BLACK



GREY



WHITE

### HOUSING

Aluminium Electrostatically applied Powder Coat

### MOUNTING RING

Aluminium Die-Cast  
Electrostatically applied Powder Coat

### HEAT SINK

Aluminium Anodised Coating

### REFLECTOR

Aluminium Anodised Specular Silver

### LED MODULE

Cree  
Optional: Philips, Osram, Tridonic

### DRIVER

Integrated: Philips, Osram, Tridonic

### DIMMING OPTIONS

DALI, Touch Dim, DSI or 1V-10V

### INPUT VOLTAGE

220V-240V AC/50Hz-60Hz

### OPERATING TEMPERATURE RANGE

-20°C to +40°C

### MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

### DRIVER LIFETIME

50,000 hours

### SYSTEM WARRANTY


5 years




MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
TRS-135X	CREE	2860lm	35W	≥80	3000K	12°, 20°, 36°, 60°	(ø135 x 239) + (ø110 x 30)mm
		2950lm			4000K		
TRS-135X	CREE	3200lm	43W	≥80	3000K	12°, 20°, 36°, 60°	(ø135 x 239) + (ø110 x 30)mm
		3320lm			4000K		

### PHOTOMETRIC DATA


#### CREE COB 35W - 12°



#### CREE COB 35W - 20°



#### CREE COB 35W - 36°



### SECTION SIZE

