

PROJECT	TYPE NO.	DATE

**SURFACE-MOUNTED DOWNLIGHT**


# TAURUS-160

-  IP20
- 
- 
-  BLACK
-  GREY
-  WHITE

- HOUSING**  
Aluminium Electrostatically applied Powder Coat
- MOUNTING RING**  
Aluminium Die-Cast  
Electrostatically applied Powder Coat
- HEAT SINK**  
Aluminium Anodised Coating
- REFLECTOR**  
Aluminium Anodised Specular Silver
- LED MODULE**  
Cree  
Optional: Philips, Osram, Tridonic
- DRIVER**  
Integrated: Philips, Osram, Tridonic
- DIMMING OPTIONS**  
Remote: DALI, Touch Dim, DSI or 1V-10V
- INPUT VOLTAGE**  
220V-240V AC/50Hz-60Hz
- OPERATING TEMPERATURE RANGE**  
-20°C to +40°C
- MAINTENANCE OF LUMEN**  
L70 50,000 hours at 25°C
- DRIVER LIFETIME**  
50,000 hours
- SYSTEM WARRANTY**  
5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
TR5-160	CREE	1600lm	20W	≥80	3000K	20°, 30°, 40°, 55°	ø160 x 180mm
		1680lm			4000K		

PHOTOMETRIC DATA				SECTION SIZE																									
<b>CREE COB 20W - 20°</b> <table border="1"> <thead> <tr> <th>H [m]</th> <th>Max [lux]</th> <th>Ø [mm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>7273</td> <td>340</td> </tr> <tr> <td>2</td> <td>1818</td> <td>680</td> </tr> <tr> <td>3</td> <td>808</td> <td>1020</td> </tr> </tbody> </table>		H [m]	Max [lux]	Ø [mm]	1	7273	340	2	1818	680	3	808	1020	<b>CREE COB 20W - 30°</b> <table border="1"> <thead> <tr> <th>H [m]</th> <th>Max [lux]</th> <th>Ø [mm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>3736</td> <td>580</td> </tr> <tr> <td>2</td> <td>934</td> <td>1180</td> </tr> <tr> <td>3</td> <td>415</td> <td>1740</td> </tr> </tbody> </table>		H [m]	Max [lux]	Ø [mm]	1	3736	580	2	934	1180	3	415	1740		
H [m]	Max [lux]	Ø [mm]																											
1	7273	340																											
2	1818	680																											
3	808	1020																											
H [m]	Max [lux]	Ø [mm]																											
1	3736	580																											
2	934	1180																											
3	415	1740																											
<b>CREE COB 20W - 40°</b> <table border="1"> <thead> <tr> <th>H [m]</th> <th>Max [lux]</th> <th>Ø [mm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2587</td> <td>800</td> </tr> <tr> <td>2</td> <td>646</td> <td>1600</td> </tr> <tr> <td>3</td> <td>287</td> <td>2400</td> </tr> </tbody> </table>		H [m]	Max [lux]	Ø [mm]	1	2587	800	2	646	1600	3	287	2400	<b>CREE COB 20W - 55°</b> <table border="1"> <thead> <tr> <th>H [m]</th> <th>Max [lux]</th> <th>Ø [mm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2007</td> <td>970</td> </tr> <tr> <td>2</td> <td>501</td> <td>1940</td> </tr> <tr> <td>3</td> <td>223</td> <td>2910</td> </tr> </tbody> </table>		H [m]	Max [lux]	Ø [mm]	1	2007	970	2	501	1940	3	223	2910		
H [m]	Max [lux]	Ø [mm]																											
1	2587	800																											
2	646	1600																											
3	287	2400																											
H [m]	Max [lux]	Ø [mm]																											
1	2007	970																											
2	501	1940																											
3	223	2910																											