

PROJECT	TYPE NO.	DATE

## SURFACE-MOUNTED DOWNLIGHT

# TAURUS-180



IP20



BLACK



GREY



WHITE

### HOUSING

Aluminium Electrostatically applied Powder Coat

### MOUNTING RING

Aluminium Die-Cast  
Electrostatically applied Powder Coat

### HEAT SINK

Aluminium Anodised Coating

### REFLECTOR

Aluminium Anodised Specular Silver

### LED MODULE

Cree  
Optional: Philips, Osram, Tridonic

### DRIVER

Integrated: Philips, Osram, Tridonic

### DIMMING OPTIONS

Remote: DALI, Touch Dim, DSI or 1V-10V

### INPUT VOLTAGE

220V-240V AC/50Hz-60Hz

### OPERATING TEMPERATURE RANGE

-20°C to +40°C

### MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

### DRIVER LIFETIME

50,000 hours

### SYSTEM WARRANTY

5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
TRS-180	CREE	2180lm	28W	≥80	3000K	20°, 30°, 40°, 55°	ø180 x 200mm
		2270lm			4000K		

## PHOTOMETRIC DATA

### CREE COB 28W – 20°

H [m]	Max [lux]	Ø [mm]
1	11487	311
2	2869	616
3	1276	928

### CREE COB 28W – 30°

H [m]	Max [lux]	Ø [mm]
1	5026	537
2	1256	1075
3	558	1613

### CREE COB 28W – 40°

H [m]	Max [lux]	Ø [mm]
1	3822	803
2	955	1607
3	424	2410

## SECTION SIZE

200mm

ø180mm