

PROJECT	TYPE NO.	DATE

TRACK SPOTLIGHT

ORION-417



IP20



90°



350°



WHITE



BLACK

HOUSING & HEAT SINK

Aluminium Electrostatically applied Powder Coat

MOUNTING RING

Aluminium Anodised Coating

REFLECTOR

LED Lens

INSTALLATION

On 3 Phase Track (PC)

LED MODULE

Cree, Optional: Philips, Osram, Tridonic

DRIVER

Integral Philips, Osram, Tridonic

DIMMING OPTIONS

DALI, Touch Dim, DSI

INPUT VOLTAGE

220V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE RANGE

-20°C to +40°C

MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

DRIVER LIFETIME

50,000 hours

SYSTEM WARRANTY


5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
ORN-417	CREE	4000lm	43W	≥80	3000K	15°, 24°, 36°	ø110 x 240mm
ORN-417	CREE	4100lm	43W	≥80	4000K	15°, 24°, 36°	ø110 x 240mm

PHOTOMETRIC DATA

CREE COB 28W - 24°



SECTION SIZE

