

PROJECT	TYPE NO.	DATE

## TRACK SPOTLIGHT

# ORION-622



IP20



90° 90°



350°



BLACK



GREY



WHITE

### HOUSING, HEAT SINK, MOUNTING RING & GEAR BOX

Aluminium Die-Cast  
Electrostatically applied Powder Coat

### REFLECTOR

Aluminium Anodised Specular Silver

### INSTALLATION

3-Phase or Single-Phase Track (PC)

### LED MODULE

Cree  
Optional: Philips, Osram, Tridonic

### DRIVER

Integral Philips, Osram, Tridonic

### INPUT VOLTAGE

220V-240V AC/50Hz-60Hz

### OPERATING TEMPERATURE RANGE

-20°C to +40°C

### MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

### DRIVER LIFETIME

50,000 hours

### SYSTEM WARRANTY


5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
ORN-622	CREE	1800lm	20W	≥80	3000K	12°, 30°, 45°, 60°	ø105 x 140mm
		1900lm			4000K		

## PHOTOMETRIC DATA

CREE COB 28W - 30°



CREE COB 28W - 45°

