

PROJECT	TYPE NO.	DATE

**TROFFER**

# CLEANLED2-S3

-  IP65
-  F  
CE
- 
- 
-  WHITE

- HOUSING**  
Cold rolled Sheet Steel  
Electrostatically applied Steel Powder Coat
- MOUNTING TYPE**  
Plaster-Recessed
- DIFFUSER**  
Fully Frosted Acrylic Low-Glare or Micro Lens
- LED MODULE**  
Osram
- DRIVER**  
Osram
- INPUT VOLTAGE**  
220V-240V AC/50Hz-60Hz
- OPERATING TEMPERATURE RANGE**  
-20°C to +40°C
- MAINTENANCE OF LUMEN**  
L70 50,000 hours at 25°C
- DRIVER LIFETIME**  
50,000 hours
- SYSTEM WARRANTY**  
5 years



\* IMAGE DISPLAYED IS S1 CLEANLED 2 FITTING

MODEL	LED	LED LUMEN	SYS. POWER	CRI	CCT	DIMENSIONS
CLED2-S3	OSRAM	1800lm	10.7W	≥80	4000K	600 x 600 x 60mm
CLED2-S3	OSRAM	2600lm	14.8W	≥80	4000K	600 x 600 x 60mm
CLED2-S3	OSRAM	3500lm	20.8W	≥80	4000K	600 x 600 x 60mm
CLED2-S3	OSRAM	4400lm	27.7W	≥80	4000K	600 x 600 x 60mm

