

PROJECT	TYPE NO.	DATE

**PANEL LIGHT**

# HPP-S1

-  IP40
-  F  
CE
- 
-  SILVER
-  WHITE

**DIFFUSER**

Anti-Glare

**MOUNTING TYPE**

T-Bar

**LED MODULE**

SMD LED

**DRIVER**

Tridonic

**DIMMING OPTIONS**

DALI, Triac Dim, or 1V-10V

**INPUT VOLTAGE**

220V-240V AC/50Hz-60Hz

**OPERATING TEMPERATURE RANGE**

-20°C to +40°C

**MAINTENANCE OF LUMEN**

L70 50,000 hours at 25°C

**DRIVER LIFETIME**

50,000 hours

**SYSTEM WARRANTY**

5 years

**AVAILABLE WITH**

- Surface-Mounting Kits
- Plaster-Recess Kits



MODEL	SYS. POWER	CRI	CCT	LED LUMEN	DIMENSIONS	NET WEIGHT
<b>HPP-S1-33</b>	33W	≥80	3000K	3200lm	1195 x 295 x 10mm	4.2kg
			4000K	3300lm		
			5000K	3350lm		
			5700K	3400lm		
<b>HPP-S1-42</b>	42W	≥80	3000K	4100lm	1195 x 295 x 10mm	4.2kg
			4000K	4200lm		
			5000K	4270lm		
			5700K	4350lm		

PHOTOMETRIC DATA	SECTION SIZE
	