






PROJECT	TYPE NO.	DATE

**TROFFER**

# SLICE-S1

 IP20  
 F  
 CE  
   
 WHITE

**CONSTRUCTION**  
Cold rolled Sheet Steel  
Electrostatically applied Powder Coat

**DIFFUSER**  
Linear fully Frosted Acrylic Lens

**LENS OPTIONS**  
Low-Glare Micro Prismatic or Frosted Micro Prismatic

**LED MODULE**  
Osram

**DRIVER**  
Philips, Osram, Tridonic

**DIMMING OPTIONS**  
DALI, Touch Dim, DSI or 1V-10V

**INPUT VOLTAGE**  
220V-240V AC/50Hz-60Hz

**OPERATING TEMPERATURE RANGE**  
-20°C to +40°C

**MAINTENANCE OF LUMEN**  
L70 50,000 hours at 25°C

**DRIVER LIFETIME**  
50,000 hours

**SYSTEM WARRANTY**  
5 years

**AVAILABLE WITH**  

- Air Slots
- Bespoke Sizing
- Surface-Mounting Kits
- Plaster-Recess Kits



MODEL	LED	LED LUMEN	SYS. POWER	CRI	CCT	DIMENSIONS
SLC-S1	OSRAM	1800lm	10.7W	≥80	4000K	1195 x 295 x 32mm
SLC-S1	OSRAM	2600lm	14.8W	≥80	4000K	1195 x 295 x 32mm
SLC-S1	OSRAM	3500lm	20.8W	≥80	4000K	1195 x 295 x 32mm
SLC-S1	OSRAM	4400lm	27.7W	≥80	4000K	1195 x 295 x 32mm

PHOTOMETRIC DATA	SECTION SIZE
