






PROJECT	TYPE NO.	DATE

TROFFER

SLICE-S3

 IP20
 F
 CE

 WHITE

CONSTRUCTION
Cold rolled Sheet Steel
Electrostatically applied Powder Coat

DIFFUSER
Linear fully Frosted Acrylic Lens

DIFFUSER OPTIONS
Low-Glare Micro Prismatic or Frosted Micro Prismatic

LED MODULE
Osram
Optional: Philips, Tridonic

DRIVER
Osram
Optional: Philips, Tridonic

DIMMING OPTIONS
DALI, Touch Dim, DSI or 1V-10V

INPUT VOLTAGE
220V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE RANGE
-20°C to +40°C

MAINTENANCE OF LUMEN
L70 50,000 hours at 25°C

DRIVER LIFETIME
50,000 hours

SYSTEM WARRANTY
5 years

AVAILABLE WITH
·Air Slots
·Bespoke Sizing
·Surface-Mounting Kits
·Plaster-Recess Kits



MODEL	LED	LED LUMENS	SYS. POWER	CRI	CCT	DIMENSIONS
SLC-S3	OSRAM	1500lm	9.1W	≥80	3000K	595 x 595 x 32mm
			8.7W		4000K	
SLC-S3	OSRAM	2200lm	14.3W	≥80	3000K	595 x 595 x 32mm
			13.7W		4000K	

PHOTOMETRIC DATA	SECTION SIZE
