

VELA-793



IP20



CE



250 x 90mm



20° 20°



BLACK



WHITE

TRIM & HOUSING

Steel
Electrostatically applied Powder Coat

MOUNTING RING

Aluminium Die-Cast
Electrostatically applied Powder Coat

ADJUSTABLE RING

Aluminium Die-Cast
Electrostatically applied Powder Coat
Adjustable Angle (Tilt $\pm 20^\circ$)

HEAT SINK

Aluminium Anodised Coating

REFLECTOR

Aluminium Anodised Specular Silver

LED MODULE

Cree

DRIVER

Remote Osram, Tridonic

DIMMING

DALI

INPUT VOLTAGE

220V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE RANGE

-20°C to +40°C

MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

DRIVER LIFETIME

50,000 hours

SYSTEM WARRANTY

5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
VLA-793	CREE	3 x 700lm	3 x 8W	≥80	3000K	18° 24° 36°	260 x 100 x 73mm
		3 x 750lm	3 x 8W		4000K		
VLA-793	CREE	3 x 1250lm	3 x 14W	≥80	3000K	18° 24° 36°	260 x 100 x 73mm
		3 x 1300lm	3 x 14W		4000K		