






PROJECT	TYPE NO.	DATE

TROFFER

ARC-S4

 IP20
 F
 CE

 WHITE

- CONSTRUCTION**
Cold rolled Sheet Steel
Electrostatically applied Powder Coat
- DIFFUSER**
Linear Prismatic fully Frosted Acrylic Low-Glare Lens
- LED MODULE**
Osram
Optional: Philips, Tridonic
- DRIVER**
Osram
Optional: Philips, Tridonic
- DIMMING OPTIONS**
DALI, Touch Dim, DSI or 1V-10V
- INPUT VOLTAGE**
220V-240V AC/50Hz-60Hz
- OPERATING TEMPERATURE RANGE**
-20°C to +40°C
- MAINTENANCE OF LUMEN**
L70 50,000 hours at 25°C
- DRIVER LIFETIME**
50,000 hours
- SYSTEM WARRANTY**
5 years
- AVAILABLE WITH**
- Bespoke Sizing
 - Surface-Mounting Kits
 - Plaster-Recess Kits



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	DIMENSIONS
ARC-S4	OSRAM	1500lm	9.1W	≥80	3000K	595 x 295 x 76mm
			8.7W		4000K	
ARC-S4	OSRAM	2200lm	14.3W	≥80	3000K	595 x 295 x 76mm
			13.7W		4000K	

PHOTOMETRIC DATA	SECTION SIZE
