

PROJECT	TYPE NO.	DATE

SURFACE-MOUNTED FLOODLIGHT

DRACO-257



IP65



GREY

HOUSING

Aluminium Die-Cast
Imports of Rubber Seals
Aluminium Profiles Recliner Bracket
Alternatively Square Aluminium Die-Cast Installation Disk
Stainless Steel Screws

LENS

High-Strength Tempered Glass Face

LED MODULE

Cree

DRIVER

Built-in LED

DIMMING OPTIONS

DMX or 1V-10V

BEAM ANGLE OPTIONS

12°, 25°, 45°, 18°x40°

INPUT VOLTAGE

100V-240V AC/50Hz-60Hz

OPERATING TEMPERATURE RANGE

-20°C to +40°C

MAINTENANCE OF LUMEN

L70 50,000 hours at 25°C

DRIVER LIFETIME

50,000 hours

SYSTEM WARRANTY

5 years



MODEL	LED	LUM. LUMENS*	SYS. POWER*	CRI	CCT	BEAM ANGLE	DIMENSIONS
DRC-257	CREE	1620lm	24W	≥80	3000K	25°	ø145 x 150mm
		1820lm			4000K		
		1980lm			6000K		
		1075lm			R.G.B		

PHOTOMETRIC DATA	SECTION SIZE
<p>CREE COB 24W - 25°</p>	
OPTIONAL ACCESSORIES	
<p>HOOD</p>	